



## TS EN 12385-4 6X19 SINIFI




6x19  
Seale



6x19  
Filler



6x19  
Warrington



6x26  
Warrington Seale

Halat çapı (mm) (mm)	En küçük kopma kuvveti (kN)					100 metresinin yaklaşık ağırlığı (kg)	
	1770 (180 kgf/mm <sup>2</sup> )		1960 (200 kgf/mm <sup>2</sup> )		2160 (220 kgf/mm <sup>2</sup> )	Lif öz	Çelik öz
	Lif öz	Çelik öz	Lif öz	Çelik öz	Çelik öz		
6	21,0	22,7	23,3	25,1	27,7	12,9	14,4
7	28,6	30,9	31,7	34,2	37,7	17,6	19,6
8	37,4	40,3	41,4	44,7	49,2	23,0	25,6
9	47,3	51,0	52,4	56,5	62,3	29,1	32,4
10	58,4	63,0	64,7	69,8	76,9	35,9	40,0
11	70,7	76,2	78,3	84,4	93,0	43,3	48,4
12	84,1	90,7	93,1	100	111	51,7	57,6
13	98,7	106	109	118	130	60,7	67,6
14	114	124	127	137	151	70,4	78,4
16	150	161	166	179	197	91,9	102
18	189	204	210	226	249	116	130
20	234	252	259	279	308	144	160
22	283	305	313	338	372	174	194
24	336	363	373	402	443	207	230
26	395	426	437	472	520	243	270
28	458	494	507	547	603	281	314
32	598	645	662	715	787	368	410
36	757	817	838	904	997	465	518
40	935	1010	1040	1120	1230	574	640
44	1130	1220	1250	1350	1490	695	774
48t	1350	1450	1490	1610	1770	827	922
52	1580	1700	1750	1890	2080	971	1080
56	1830	1980	2030	2190	2410	1130	1250
60	2100	2270	2330	2510	2770	1290	1440