



GENEL AMAÇLI ÇELİK HALATLAR


TS EN 12385-4 6X36 SINIFI



6x31
Warrington Seal



6x36
Warrington Seal



6x41
Warrington Seal

Halat çapı (mm)	En küçük kopma kuvveti (kN)					100 metresinin yaklaşık ağırlığı (kg)	
	1770 (180 kgf/mm ²)		1960 (200 kgf/mm ²)		2160 (220 kgf/mm ²)		
	Lif öz	Çelik öz	Lif öz	Çelik öz	Çelik öz	Lif öz	Çelik öz
8	37,4	40,3	41,4	44,7	49,2	23,5	26,2
9	47,3	51,0	52,4	56,5	62,3	29,7	33,1
10	58,4	63,0	64,7	69,8	76,9	36,7	40,9
11	70,7	76,2	78,3	84,4	93,0	44,4	49,5
12	84,1	90,7	93,1	100	11	52,8	58,9
13	98,7	106	109	118	130	62,0	69,1
14	114	124	127	137	151	71,9	80,2
16	150	161	166	179	197	94,0	105
18	189	204	210	226	249	119	133
20	234	252	259	279	308	147	164
22	283	305	313	338	372	178	198
24	336	363	373	402	443	211	236
26	395	426	437	472	520	248	276
28	458	494	507	547	603	288	321
32	598	645	662	715	787	376	419
36	757	817	838	904	997	476	530
40	935	1010	1040	1120	1230	587	654
44	1130	1220	1250	1350	1490	711	792
48	1350	1450	1490	1610	1770	846	942
52	1580	1700	1750	1890	2080	992	1110
56	1830	1980	2030	2190	2410	1150	1280
60	2100	2270	2330	2510	2770	1320	1470