



TS EN 12385-4 8X19 SINIFI



8x19
Seale



8x19
Filler



8x19
Warrington



8x26
Warrington Seale

Halat çapı (mm) (mm)	En küçük kopma kuvveti (kN)					100 metresinin yaklaşık ağırlığı (kg)	
	1770 (180 kgf/mm ²)		1960 (200 kgf/mm ²)		2160 (220 kgf/mm ²)		
	Lif öz	Çelik öz	Lif öz	Çelik öz	Çelik öz	Lif öz	Çelik öz
8	33,2	40,3	36,8	44,7	49,2	21,8	26,0
9	42,0	51,0	46,5	56,5	62,3	27,5	33,0
10	51,9	63,0	57,4	69,8	76,9	34,0	40,7
11	62,8	76,2	69,5	84,4	93,0	41,1	79,2
12	74,7	90,7	82,7	100	11	49,0	58,6
13	87,6	106	97,1	118	130	57,5	68,8
14	102	124	113	137	151	66,6	79,8
16	133	161	147	179	197	87,0	104
18	168	204	186	226	249	110	132
20	207	252	230	279	308	136	163
22	251	305	278	338	372	165	197
24	299	363	331	402	443	196	234
26	351	426	388	472	520	230	275
28	407	494	450	547	603	267	319
32	531	645	588	715	787	348	417
36	672	817	744	904	997	441	527
40	830	1010	919	1120	1230	544	651
44	1000	1220	1110	1350	1490	658	788
48	1200	1450	1320	1610	1770	783	938
52	1400	1700	1550	1890	2080	919	1100
56	1630	1980	1800	2190	2410	1070	1280
60	1870	2270	2070	2510	2770	1220	1470