



PRODUCT CATALOG

TUF-MAX XL

- ▶ Greater fatigue resistance over standard 6 strand ropes
- ▶ Dual coated core prevents internal nicking and notching
- ▶ Superior strength
- ▶ Excellent fatigue resistance
- ▶ Excellent surface mining shovel hoist rope
- ▶ Guaranteed to out perform competing designs



If you think our standard TUF-MAX was good, wait until you try our TUF-MAX XL.

Our new TUF-MAX XL has the highest strength of the TUF-MAX family by more than 15%. The matched lay state of the art design results in greater metallic area and makes this rope a logical choice for the most severe digging conditions. Through this design, internal contact and nicking is kept to a minimum which results in a higher rope breaking strength. Keeping your shovel productive until your next PM.

There's no other shovel rope comparable. Ask about our guarantee today and try one.

TUF-MAX Strength and Weights Chart (mm)

Diameter (mm)	Approx Weight (kg/m)	Minimum Breaking Force 1960 Grade (kN)
45	8.44	1504
48	9.67	1708
51	11.0	1931
54	12.4	2171
57	13.9	2509
60	15.5	2687
64	17.3	2954
67	19.0	3239
70	20.8	3532
73	22.8	3844

Union International, a WireCo WorldGroup brand, produces wire rope for a variety of applications – each with their own exacting specifications. All of our products are manufactured in a state-of-the-art wire rope production facility in Wuhan, China.